

- (1) Veröffentlichungsnummer.
- 11 Publication number:
- (11) Numéro de publication;

0 592 620

Internationale Anmeldung veræffentlicht durch die Weltorganisation fßr geistiges Eigentum unter der Nummer:

WO 93/17878 (art.158 des EPf).

International application published by the World Intellectual Property Organisation under number:

WO 93/17878 (art.158 of the EPC).

Demande internationale publieà par l'Organisation Mondiale de la Propriàtà sous le numèro:

WO 93/17878 (art.158 de la CBE).

WORLD INTELLECTUAL PROPERTY ORGANIZATION



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 5:

B42D 15/10

A1

(11) International Publication Number: WO 93/17878

(43) International Publication Date: 16 September 1993 (16.09.93)

(21) International Application Number: PCT/US93/01172

(22) International Filing Date: 9 February 1993 (09.02.93)

(30) Priority data: 07/847,165 5 March 1992 (05.03.92) US

(71) Applicant: BAXTER INTERNATIONAL INC. [US/US]; One Baxter Parkway, Deerfield, IL 60015 (US).

(72) Inventor: LEUENBERGER, Mark; 5403 Virginia, Gurnee, IL 60031 (US).

(74) Agents: PRICE, Bradford, R., L. et al.; One Baxter Parkway, Deerfield, IL 60015 (US).


(81) Designated States: CA, JP, European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, 1E, IT, LU, MC, NL, PT, SE).

Published With international search report.

(54) Title: BLOOD PACK LABELS

(57) Abstract

A label (12) for a blood pack (10) comprising a microporous plastic film including a matrix of interconnected pores for allowing gas to flow into and out of the blood pack (10) through a labeled area. The pores allow ink to be absorbed at least on an outer surface of the label (12) allowing the label (12) to be printed and/or written on. The labels of the present invention have breathability with respect to gas that is similar to paper. However, the label (12) is more durable than a paper label in that it can tolerate moisture, abrasion, temperature extremes, dimensional changes, and the like. Accordingly, the labels do not crack or wrinkle as easily as paper labels.



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	FR	France	MR	Mauritania
AU	Australia	GA	Gabon	MW	Malawi
BB	Barbados	GB	United Kingdom	NL	Netherlands
BE	Belgium	GN	Guinea	NO	Norway
BF	Burkina Faso	GR	Greece	NZ	New Zealand
BC	Bulgaria	HU	Hungary	PL	Poland
BJ	Benin	ΙE	Ireland	PŤ	Portugal
BR	Brazil '	ıπ	Italy	RO	Romania
CA	Canada	JP	Japan	RU	Russian Federation
CF	Central African Republic	KP	Democratic People's Republic	SD	Sudan
CC	Congo		of Korca	SE	Sweden
CH	Switzerland	KR	Republic of Korea	sk	Slovak Republic
CI	Côte d'Ivoire	KZ.	Kazakhstan	SN	Senegal
CM	Cameroon	t.)	Liechtenstein	SU	Soviet Union
CS	Czechoslovakia -	LK	Sri Lanka	ΥD	Chad
CZ	Czech Republic	เ.บ	Laxembourg	TG	Togo
DE	Germany	MC	Monaco	UA	Ukraine
DK	Denmark	MC	Madagascar	US	United States of America
ES	Spain	MI.	Mali	٧N	Vict Nam
Fſ	Finland	MN	Mongolia		

- 1 -

BPECIFICATION

TITLE

Blood Pack Labels

BACKGROUND OF THE INVENTION

5

10

15

20

25

30

The present invention relates to blood packs generally. More specifically, the present invention relates to labels for blood packs.

It is known to house blood components in flexible plastic containers. These containers referred to as either blood packs or blood bags can be used to receive a blood component, process the blood component, store the blood component, and assist in infusing the blood component into a recipient. Of course, it is necessary to provide some means for identifying certain information on the blood pack, e.g., the type of storage solution, anticoagulant, or blood component, the collection date, manufacturer's product code and lot number, etc.

To this end, it is known to provide labels for blood packs. Typically, these labels have heretofore comprised a paper substrate that is secured to the container. These paper labels provide many characteristics that are necessary and/or desirable for a blood pack label.

Blood packs must provide a container that allows gas transmission through the container in order to maintain the viability of the cells to be housed therein. In this regard, it is necessary that the bag allow carbon dioxide to flow out of the blood pack and oxygen to flow therein. Paper provides a substrate that allows for a flow of gas through the labeled area of the blood pack; a paper label does not decrease the effective area of the bag that allows gas transmission beyond acceptable limits.

Paper also provides a surface that can be written or printed on. Thus, a paper label provides a substrate

- 2 -

that allows one to easily indicate necessary information on the blood pack. In this regard, the label typically will receive printed as well as handwritten information. It is also known to use bar codes on such labels.

5

10

15

20

25

30

Paper, however, does exhibit certain disadvantages when used as a label for a blood pack. Paper labels are not very durable to moisture, abrasion, temperature extreme, and are not elastic to allow for dimensional changes that occur to the blood pack. It is known to process the blood components stored within the blood packs by centrifuging the bag in addition to other processes. During such processes the labels can become wet and subjected to extreme temperatures. Paper labels can crack or wrinkle during such processes. The cracking or wrinkling of a label is especially detrimental to the use of bar codes on such labels. Unless a smooth uninterrupted surface is provided, the bar codes may be unreadable by a bar code reader. This forces manual entering of data into a computer thus increasing the chance for errors.

There are a number of other requirements that a blood pack label must meet. Some such requirements are set forth in the labeling requirements that have been instituted by the: American Blood Commission's Uniform Labeling Guidelines, 1985; or NBTS "Spec for Uniform Labeling of Blood and Blood Products."

It is also desirable that blood pack labels be easily applied to the blood pack. Such labels must also endure the typical manufacturing processing conditions that are typically utilized. In this regard, the bag and label must be sterilizable. Further, the labels must be able to withstand the processing conditions that the containers may be subjected to by the customer, for

- 3 -

example, centrifugation, liquid freezing, water bath thawing to name a few.

SUMMARY OF THE INVENTION

5

10

15

20

30

The present invention provides a label for a blood pack that provides the desirable characteristics of a paper label but not the disadvantages. The labels of the present invention have a permeability with respect to gas that is similar to paper. Additionally, the label will accept printing as easily as paper. However, the label is more durable than a paper label in that it can tolerate moisture, abrasion, temperature extremes, dimensional changes, and the like. Accordingly, the labels do not crack or wrinkle as easily as paper labels.

The present invention provides a label for a blood pack comprising a microporous plastic film including a matrix of interconnected pores for allowing gas to flow into and out of the blood pack through a labeled area. The pores allow ink to be absorbed at least on an outer surface of the label allowing the label to be printed and/or written on.

In an embodiment, the label includes either a pressure or heat sensitive adhesive on a bottom surface thereof for allowing the label to be secured to the blood pack.

In an embodiment, the label includes one or more bar codes printed thereon.

The present invention also provides a blood pack that includes a label that is constructed from a microporous plastic film including a matrix of interconnected pores for allowing gas to flow into and out of the blood pack through a labeled area. At least the pores located on an outer surface of the label are

- 4 -

so constructed and arranged to receive ink allowing the label to be written on.

In an embodiment, the label is secured to the blood pack by a pressure or heat sensitive adhesive.

5

10

15

20

25

30

The present invention also provides a method for labeling a blood pack comprising the steps of: applying a label comprising microporous plastic film to the blood pack; allowing gas to flow through pores in the label into and out of the blood bag; and writing on the label by causing ink to be received within pores located on an outer surface of the label.

An advantage of the present invention is that the microporous surface of the label also allows other labels to be applied to the original bag labels such that their adhesives utilize the porous surface of the first label to form permanent bonds.

Another advantage of plastic labels of the present invention is that the label does not contain some of the typical undesirable chemical constituents of paper, such as formaldehyde.

Additional features and advantages of the present invention are described in, and will be apparent from, the detailed description of the presently preferred embodiments and from the drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

Figure 1 illustrates a blood pack including the label of the present invention.

Figure 2a is a photomicrograph of a surface magnification (3,000 times) of the labeling surface of a current paper label.

Figure 2b is a photomicrograph of a surface magnification (3,000 times) of the labeling surface of an embodiment of a label of the present invention.

- 5 -

Figure 3a is a photomicrograph of a cross-sectional magnification (300 times) view of a current paper label including an adhesive layer.

Figure 3b is a photomicrograph of a magnification (300 times) of the labeling surface of the paper label of Figure 3a.

5

10

15 ·

20

25

30

Figure 4a is a photomicrograph of a cross-sectional magnification (300 times) view of an embodiment of a label including an adhesive layer of the present invention.

Figure 4b is a magnification (300 times) of the labeling surface of the embodiment of the label of Figure 4a.

Figure 5 is a surface magnification (10,000 times) at higher magnification of an embodiment of the label of the present invention.

DETAILED DESCRIPTION

OF THE PRESENTLY PREFERRED EMBODIMENTS

The present invention provides an improved label for blood packs and the like. The label exhibits the desirable properties of paper labels, but does not also exhibit a number of disadvantages associated with paper, such as lack of durability.

The labels of the present invention provide gas transmission, permeability through the label, into and out of the blood pack, similar to a paper label. Further, the labels are as easily printed on, either by writing or a printing process, as a paper label. However, the labels of the present invention are more durable with respect to moisture, abrasion, temperature extremes, and dimensional changes than are paper labels. Accordingly, the labels do not crack and wrinkle as easily as paper labels.

- 6 -

Figure 3a is a photomicrograph of a cross-sectional magnification (300 times) view of a current paper label including an adhesive layer.

Figure 3b is a photomicrograph of a magnification (300 times) of the labeling surface of the paper label of Figure 3a.

5

10

15

20

25

30

Figure 4a is a photomicrograph of a cross-sectional magnification (300 times) view of an embodiment of a label including an adhesive layer of the present invention.

Figure 4b is a magnification (300 times) of the labeling surface of the embodiment of the label of Figure 4a.

Figure 5 is a surface magnification (10,000 times) at higher magnification of an embodiment of the label of the present invention.

DETAILED DESCRIPTION

OF THE PRESENTLY PREFERRED EMBODIMENTS

The present invention provides an improved label for blood packs and the like. The label exhibits the desirable properties of paper labels, but does not also exhibit a number of disadvantages associated with paper, such as lack of durability.

The labels of the present invention provide gas transmission, permeability through the label, into and out of the blood pack, similar to a paper label. Further, the labels are as easily printed on, either by writing or a printing process, as a paper label. However, the labels of the present invention are more durable with respect to moisture, abrasion, temperature extremes, and dimensional changes than are paper labels. Accordingly, the labels do not crack and wrinkle as easily as paper labels.

- 7-

The labels of the present invention comprise a microporous plastic film. The microporous plastic film is constructed by processing methods that cause the material to consist of a matrix of interconnected microsize pores that allow gases and vapors to flow freely therethrough. A number of processes can be used to create such a film including, but not limited to, stretching the film, radiation treatment of the film, and addition of film additives such as fillers that may or may not be removed from the film during processing.

5

10

15

20

25

30

Referring now to Figure 1, a blood pack 10 including the blood label 12 of the present invention is illustrated. As illustrated, the blood pack 10 defines a container for receiving and storing a blood component. The blood pack 10 is constructed from a plastic material, such as plasticized polyvinyl chloride. Such blood packs are available from Baxter Healthcare Corporation, Fenwal Division, Deerfield, Illinois.

The label 12 is secured to the blood pack 10 to allow one to identify the blood pack. To this end, as illustrated, the label can be printed on, as well as include a bar code. It is also common practice to write on the label. The label 12 of the present invention allows one to easily identify the blood pack for inventory purposes, to determine what is in the blood pack, expiration date, and the like.

The label 12 includes interconnected microsize pores that allow gases and vapors to flow freely through the blood pack 10 and label 12. In this regard, carbon dioxide generated within the container will flow out of the blood pack 10 and oxygen necessary for the cell's viability will flow into the blood pack. The size of the pores and/or controlled coatings between the adhesive

_ 8_

layer and back side of the label can be varied to control the rate of gas exchange. As set forth in detail below, the labels 12 of the present invention provide sufficient gas permeability.

5

10

15

20

25

30

It has been found that the microporous label of the present invention meets the necessary and desirable requirements for a blood pack label. These requirements include being non-removable, in an intact state, from the pack, or not reappliable, tamper evident, to another bag once removed by the customer.

Due to the microporous structure of the label, the label can easily be written on or printed on. To this end, the pores near the outer surface of the label will receive ink and therefore allow the label to be written on or printed on, such as with a bar code. In this regard, the label will accept writing or ink stamping on its surface and will not smear five seconds after being printed on with a variety of means.

The label when scanned with a bar code reader will read accurately. An advantage of the label of the present invention over a paper label is that the label will not wrinkle or crack during processing conditions and accordingly, can be bar code read accurately by a standard bar code reader multiple times without deterioration of read rates.

The label is visually acceptable from an aesthetic standpoint and is not adversely effected by manufacturing and processing conditions, i.e., it will not wrinkle, crack, split, scuff, fade, etc., during processing conditions.

The label additionally complies with the American Blood Commission's "Uniform Labelling Guidelines" (1985 & Draft 1989).

5

10

15

20

The labels of the present invention can also be applied using currently available labeling equipment and methods with minimal modification. To this end, the label can either include a pressure or heat sensitive adhesive to be sealed to the blood pack.

The label is not adversely affected by processing conditions of manufacturing. These processing conditions include sterilization, such as: steam sterilization in plastic overwraps; steam pasteurization, in foil pouch; ozone pasteurization; Eto sterilization; and Gamma or E-Beam sterilization.

The labels of the present invention are not adversely affected by warehouse/shipping conditions during useful shelf life of finished product (i.e., 30-36 months) or raw label materials before application (i.e., 2 years).

An example of a microporous label material that can be used in the present invention includes Teslin, a microporous polyolefin film manufactured by PPG Industries.

Microporous labels of the present invention were tested per ASTM #D3985 for material gas permeability.

BAG AND LABEL MATERIAL GAS PERMEABILITY

UNITS = (CC/1001N²/24 HOURS)*

25			Bag Materials							
	Label Materials	Plasticized PVC		Plasticized PVC		<u>Polyolefin</u>		Plasticized PVC		
		02*	CO°*	0,*	CO2*	0°*	CO2*	0,*	CO:*	
30	Paper Labels	-								
	1	23	132	18	186	•	-	34	537	
	2	-	-	-	•	91	426	_	-	
	3	-	-	-	-	123	616	-	-	

- 10-

Microporous	1							
<u>Labels</u>								
4	27	220	54	703	-	•	56	506
5	24	204	59	285	222	667	52	383
6	26	209	49	285	101	682 ·	72	660
7	27	185	56	318	114	765	60	572

5

25

30

Tested per ASTM #D3985 for 0,

Through Label Material and Bag Material Combined (Modified for CO₂ by Using Infrared Detector)

- Paper Label available from DRG, Madison, Wisconsin under the designation Newton Falls paper with heat activated adhesive.
 - 2. Paper label available from Modern Press, Sioux Falls, South Dakota, under the designation Champion Kromekote paper with pressure sensitive adhesive.
- 3. Paper label available from Modern Press, Sioux Falls, South Dakota, under the designation Champion Kromekote paper with pressure sensitive adhesive.
 - 4. Microporous Film Label from 3M with pressure sensitive adhesive.
 - 5. Microporous Film Label from 3M with pressure sensitive adhesive.
- Microporous Film Label from Avery Label, Azusa, California with pressure sensitive adhesive.
 - 7. Microporous Film Label from Avery Label, Azusa, California with pressure sensitive adhesive.

Referring now to Figures 2-5, electron microscopy photographs at different magnifications for currently used paper labels and labels of the present invention are illustrated. The label of the present invention illustrated in the photos (Figures 2b, 4a, 4b, and 5) are made with Teslin from PPG Industries. The microphotographs are consistent with the test results set forth above demonstrating porosity at least as good as the porosity of paper labels.

- 11 -

It should be understood that various changes and modifications to the presently preferred embodiments described herein will be apparent to those skilled in the art. Such changes and modifications can be made without departing from the spirit and scope of the present invention and without diminishing its attendant advantages. It is therefore intended that such changes and modifications be covered by the appended claims.

5

_ 12 _

I CLAIM:

5

10

15

20

30

- A label for a blood pack comprising:
- a microporous plastic film including a matrix of interconnected pores for allowing gas to flow into and out of the blood pack through a labeled area.
- 2. The label of Claim 1 wherein the pores allow ink to be absorbed at least on an outer surface of the label allowing the label to be written on.
- 3. The label of Claim 1 wherein the label includes a pressure sensitive adhesive on a bottom surface for allowing the label to be secured to the blood pack.
- 4. The label of Claim 1 wherein the label includes a heat sensitive adhesive on a bottom surface for allowing the label to be secured to the blood pack.
- 5. The label of Claim 1 wherein the label includes a bar code printed thereon.
- 6. A blood pack including a label wherein the label is constructed from a microporous plastic film including a matrix of interconnected pores for allowing gas to flow into and out of the blood pack through a labeled area, at least pores located on an outer surface of the label being so constructed and arranged to receive ink allowing the label to be written on.
- The blood pack of Claim 6 wherein the label is
 secured to the blood pack by a pressure sensitive material.
 - 8. The blood pack of Claim 6 wherein the label is heat sealed to the blood pack.
 - 9. The blood pack of Claim 6 wherein the label includes a bar code printed thereon.
 - 10. A method for labeling a blood pack comprising the steps of:

_ 13 _

applying a label comprising microporous plastic film to the blood pack;

allowing gas to flow through pores in the label into and out of the blood pack; and

writing on the label by causing ink to be received within pores located on an outer surface of the label.

- 11. The method of Claim 10 including the step of sealing the label to the blood pack by using a heat sensitive adhesive.
- 10 12. The method of Claim 10 including the step of sealing the label to the blood pack by using a pressure sensitive adhesive.
 - 13. The method of Claim 10 including the step of placing a bar code on the label.
- 14. The method of Claim 10 including the step of applying a second label over the label by applying an adhesive to the outer surface of the label and causing a portion of the adhesive to be received by the pores located on the outer surface of the label.

20

5




FIG. 1 SUBSTITUTE SHEET

2/5 FIG. 2a





FIG. 2b



SUBSTITUTE SHEET

3/5

FIG. 3a




FIG. 3b




FIG. 4a






FIG. 4b



SUBSTITUTE SHEET

FIG. 5



INTERNATIONAL SEARCH REPORT

PCT/US93/01172

	SSIFICATION OF SUBJECT MATTER	
US CL	:B42D 15/10 :283/081	
According	to International Patent Classification (IPC) or to both national classification	fication and IPC
	LDS SEARCHED	
Minimum o	ocumentation searched (classification system followed by classification	ion symbols)
U.S. :	283/081	
Documents	tion searched other than minimum documentation to the extent that su	ah da
Documenta	mon searched other than minum documentation to the extent that bu	en documents are included in the fields searched
Electronic (data base consulted during the international search (name of data base).	se and, where practicable, search terms used)
C. DOC	CUMENTS CONSIDERED TO BE RELEVANT	
Category*	Citation of document, with indication, where appropriate, of t	he relevant passages Relevant to claim I
x	US,A, 4,880,425 (Kuhlemann et al.) 14 Nove Col. 3, lines 20-30 and Col. 5, lines 35-45.	ember 1989 Note 1-14
	<u>.</u>	
		ļ
Fun	her documents are listed in the continuation of Box C.	ee patent family annex.
• s _i	pecial categories of cited documents:	document published after the international filing date or prior
	reument defining the general state of the art which is not considered prin- be part of particular relevance	and not in conflict with the application but cited to understand to ciple or theory underlying the invention.
	relies document muhlished on or after the international filing date "X" doct	ment of particular relevance; the claimed invention cannot idered novel or cannot be considered to involve an inventive st
°L' de	recurrent which may throw doubts on priority claim(s) or which is when took to establish the publication date of another citation or other	n the document is taken alone
27	ecial reason (as specified) Y doc com	ment of particular relevance; the claimed invention cannot idered to involve an inventive step when the document
	exment referring to an oral disclosure, use, exhibition or other com	bined with one or more other such documents, such combinat g obvious to a person skilled in the art
°P° de	recument published prior to the international filing date but later than *&* does o priority date claimed	ament member of the same patent family
Date of the	e actual completion of the international search Date of mail	ing of the international search report
12 APRI	L 1993 17 MAT	1535
		ficer / / / / / / / / / / / / / / / / / / /
Box PCT	oner of Patents and Trademarks	BELL
_	No. NOT APPLICABLE Telephone N	lo. (703) 308-1148
	1 telephone is	. (100) 500 1140 7

Form PCT/ISA/210 (second sheet)(July 1992)+